



Dell EMC PowerSwitch N1500 Series Switches

Extending enterprise features to small and mid-sized businesses

The N1500 switch series offers a power-efficient Gigabit Ethernet (GbE) network-access switching solution with integrated 10GbE uplinks. With high-performance capabilities and wire-speed performance, utilizing a non-blocking architecture to easily handle unexpected traffic loads, the switches offer simple management and scalability via an 40Gbps (full-duplex) high availability stacking architecture that allows management of up to four switches from a single IP address. An integrated 80PLUS-certified power supply and features such as Energy-Efficient Ethernet and short cable detection provide energy efficiency to help decrease power and cooling costs.

Modernize campus network architectures

Modernize campus network architectures with a power-efficient and resilient 1/10GbE switching solution with Power over Ethernet Plus (PoE+). Select N1500 models offer 24 or 48 ports of PoE+ to deliver clean power to network devices such as wireless access points (APs), Voice-over-IP (VoIP) handsets, video conferencing systems and security cameras.

Leverage familiar tools and practices

All N-Series switches include Dell EMC Networking OS6, designed for easier deployment, greater interoperability and a lower learning curve for network administrators. OS6 common command line interface (CLI) and graphic user interface (GUI) using a well-known command language gets skilled network administrators productive quickly. With USB auto-configuration, network administrators can rapidly deploy mirrored configurations to numerous devices by simply inserting a USB key.

Deploy with confidence at any scale

N1500 series switches help create performance assurance with a data rate up to 176Gbps (full duplex) and a forwarding rate up to 164Mpps. Scale easily by stacking with 10GbE ports. Switch stacks of up to 200 1GbE ports can be managed from a single screen using the highly available stacking architecture for high-density aggregation with seamless redundant availability. N-Series switches help provide certainty with a lifetime warranty that covers software upgrades, hardware repair or replacement, and optics and cables purchased with the switch.*

Hardware, performance and efficiency

- Up to 48 line-rate GbE RJ-45 ports and four integrated 10GbE SFP+ ports.
- Up to 48 ports of PoE+ with an optional external power supply.
- Up to 200 1GbE ports in a 4-unit stack for high-density, high-availability in IDFs, MDFs and wiring closets.
- Non-stop forwarding and fast failover in stack configurations.
- Energy-Efficient Ethernet and lower power PHYs reduce power to inactive ports and idle links, providing energy savings from the power cord to the port.
- Fresh Air compliance for operation in environments up to 113°F (45°C) helps reduce cooling costs in temperature-constrained deployments.

*Select Networking products carry a Lifetime Limited Warranty with Basic Hardware Service (repair or replacement) for life. Repair or replacement does not include troubleshooting, configuration, or other advanced service provided by Dell EMC ProSupport. For details, visit <https://www.dell.com/en-us/work/shop/networkingwarranty/cp/networkingwarranty>.

Deploying, configuring and managing

- USB auto-configuration rapidly deploys the switch without setting up complex TFTP configurations or sending technical staff to remote offices.
- Management via an intuitive and familiar CLI, embedded web server (GUI), SNMP-based management console application (including Dell EMC OpenManage Network Manager), Telnet or serial connection.
- Private VLAN extensions and Private VLAN Edge support.

Product	Description
N1500 series	N1524: 24x RJ45 10/100/1000Mb auto-sensing ports, 4x SFP+ ports, 1 integrated 40W PSU N1524P: 24x RJ45 10/100/1000Mb PoE+ (up to 30.8w) auto-sensing ports, 4x SFP+ ports, 1 integrated 600W PSU (requires C15 plug) N1548: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x SFP+ ports, 1 integrated 100W PSU N1548P: 48x RJ45 10/100/1000Mb PoE+ (up to 30.8w) auto-sensing ports, 4x SFP+ ports, 1 integrated 600W PSU (requires C15 plug)
Power cords	C13 to NEMA 5-15, 3M C13 to C14, 2M C15 to NEMA 5-15, 2M (C15 for POE N-Series only)
Power supplies (optional)	RPS720 external power supply for N1500 non-POE (720 watts): N1524 and N1548 (sold separately) MPS1000 external power supply for N1500 PoE+ switches (1000 watts): N1524P and N1548P (sold separately)
Optics (optional)	Transceiver, SFP, 1000BASE-T Transceiver, SFP, 1000BASE-SX, 850nm wavelength, up to 550m reach Transceiver, SFP, 1000BASE-LX, 1310nm wavelength, up to 10km reach Transceiver, SFP, 1000BASE-ZX, 1550nm wavelength, up to 80km reach Transceiver, SFP+, 10GbE, SR, 850nm wavelength, up to 300m reach Transceiver, SFP+, 10GbE, LR, 1310nm wavelength, up to 10km reach Transceiver, SFP+, 10GbE, ER, 1550nm wavelength, up to 40km reach
Cables (optional)	Dell Technologies Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct

Technical specifications

Hardware specifications

Physical

4 integrated front 10GbE SFP+ dedicated ports,
2 10GbE can be used as stacking ports
USB (Type A) port for configuration via USB flash drive
Auto-negotiation for speed and flow control
Auto MDI/MDIX, port mirroring
Flow-based port mirroring
Broadcast storm control
Energy-Efficient Ethernet per port settings
Redundant variable speed fans
Air flow: I/O to power supply
Integrated power supply: 40W AC (N1524), 100W AC (N1548), 600W AC (N1524P, N1548P)
RJ45 console port with RS232 signaling (RJ-45 to female DB-9 connector cable included)
Dual firmware images on-board
Switching engine model: Store and forward

Chassis

Size (1RU, H x W x D):
N1524 and N1548: 1.7 in x 17.3 in x 10.1 in (43.2 mm x 440.0 mm x 257.0 mm)
N1524P and N1548P: 1.7 in x 17.3 in x 15.2 in (43.2 mm x 440.0 mm x 387.0 mm)
Approximate weight: 6.6lbs/3kg (N1524), 12.8lbs/5.8kg (N1524P), 8.8lbs/4kg (N1548), 15.4lbs/7kg (N1548P)
Rack mounting kit with 2 mounting brackets, bolts and cage nuts

Environmental

Power supply efficiency: 80% or better in all operating modes
Max. thermal output (BTU/hr): 103.1 (N1524), 2972 (N1524P), 152.2 (N1548), 5824.3 (N1548P)
Power consumption max (watts): 30.2 (N1524), 871 (N1524P), 44.6 (N1548), 1704 (N1548P)
Operating temperature: 32° to 113°F (0° to 45°C)
Operating humidity: 95%
Storage temperature: -40° to 149°F (-40° to 65°C)
Storage relative humidity: 85%

Performance

MAC addresses: 16K
Static routes: 256 (IPv4)/128 (IPv6)
Dynamic routes: 256 (IPv4)
Switch fabric capacity: 128Gbps (N1524 and N1524P) (full duplex); 176Gbps (N1548 and N1548P)
Forwarding rate: 128Mpps (86 Gbps) N1524 and N1524P
164Mpps (110 Gbps) N1548 and N1548P
Link aggregation: 64 LAG groups, 144 dynamic ports per stack, 8 member ports per LAG
Priority queues per port: 8
Line-rate Layer 2 switching: All (non-blocking)
Line-rate Layer 3 routing: All (non-blocking)
Flash memory: 256MB
Packet buffer memory: 1.5MB
CPU memory: 1GB
RIP routing interfaces: 128
VLAN routing interfaces: 128
VLANs supported: 512

Protocol-based VLANs: Supported
ARP entries: 2,048 (IPv4)/512 (IPv6)
NDP entries: 400
Access control lists (ACL): Supported
MAC and IP-based ACLs: Supported
Time-controlled ACLs: Supported
Max number of ACLs: 100
Max ACL rules system-wide: 2,048
Max rules per ACL: 1,023
Max ACL rules per interface (IPv4): 1,023 (ingress), 1,023 (egress)
Max ACL rules per interface (IPv6): 512 (ingress), 509 (egress)
Max VLAN interfaces with ACLs applied: 24

IEEE compliance

802.1AB LLDP
Dell Voice VLAN
Dell ISDP (inter-operates with devices running CDP)
802.1D Bridging, Spanning Tree
802.1p Ethernet Priority (User Provisioning and Mapping)
Dell Adjustable WRR and Strict Queue Scheduling
802.1Q VLAN Tagging, Double VLAN Tagging, GVRP
802.1S Multiple Spanning Tree (MSTP)
802.1v Protocol-based VLANs
802.1W Rapid Spanning Tree (RSTP)
Dell RSTP-Per VLAN (compatible with Cisco's RPVST+)
Dell Spanning tree optional features: STP root guard, BPDU guard, BPDU filtering
802.1X Network Access Control, Auto VLAN

IT Lifecycle Services for Networking

Experts, insights and ease

Our highly trained experts, with innovative tools and proven processes, help you transform your IT investments into strategic advantages.



Plan & Design

Let us analyze your multivendor environment and deliver a comprehensive report and action plan to build upon the existing network and improve performance.



Deploy & Integrate

Get new wired or wireless network technology installed and configured with ProDeploy. Reduce costs, save time, and get up and running fast.



Educate

Ensure your staff builds the right skills for long-term success. Get certified on Dell EMC Networking technology and learn how to increase performance and optimize infrastructure.



Manage & Support

Gain access to technical experts and quickly resolve multivendor networking challenges with ProSupport. Spend less time resolving network issues and more time innovating.



Optimize


Maximize performance for dynamic IT environments with Dell EMC Optimize. Benefit from in-depth predictive analysis, remote monitoring and a dedicated systems analyst for your network.



Retire

We can help you resell or retire excess hardware while meeting local regulatory guidelines and acting in an environmentally responsible way.

Learn more at DellTechnologies.com/Services



[Learn more](#) about Dell EMC Networking solutions



[Contact](#) a Dell Technologies Expert



[View more](#) resources



Join the conversation with [@DellNetworking](#)



Dell EMC PowerSwitch N2200-ON Series Switches

Cost-effective open networking Multigigabit Ethernet switches for modernizing and scaling infrastructure

The N2200-ON switch series offers a power-efficient Multigigabit Ethernet network-access switching solution with integrated 25GbE uplinks. With high-performance capabilities and wire-speed performance, utilizing a non-blocking architecture to easily handle unexpected traffic loads, the switches offer simple management and scalability via an 160Gbps (full duplex) high availability stacking architecture that allows management of up to twelve switches from a single IP address. An integrated 80PLUS Platinum certified power supply provides energy efficiency to help decrease power and cooling costs.

Modernize campus network architectures

Modernize campus network architectures with a power-efficient and resilient 1/2.5/25GbE switching solution with 802.3bt Type-3 (60W) Power over Ethernet. PoE ports can deliver clean power to network devices such as wireless access points (APs), Voice-over-IP (VoIP) handsets, video conferencing systems, security cameras, LED luminaries and many more. For greater interoperability in multivendor networks, N2200-ON switches offer the latest open-standard protocols.

Leverage familiar tools and practices

All N-Series switches include Dell EMC Networking OS6, designed for easier deployment, greater interoperability and a lower learning curve for network administrators. One common command line interface (CLI) and graphic user interface (GUI) using a well-known command language gets skilled network administrators productive quickly. With USB auto-configuration, network administrators can rapidly deploy mirrored configurations to numerous devices by simply inserting a USB key. N2200-ON switches also support the Open Network Install Environment (ONIE), enabling installation of alternate network operating systems.

Deploy with confidence at any scale

N2200-ON series switches help create performance assurance with a data rate up to 600Gbps (full duplex) and a forwarding rate up to 833Mpps. Scale easily with built-in rear stacking ports. Switch stacks of up to 624 1/2.5/25GbE ports can be managed from a single screen using the highly-available stacking architecture for high-density aggregation with seamless redundant availability.

N-Series switches help provide certainty with a lifetime warranty that covers software upgrades, hardware repair or replacement, and optics and cables purchased with the switch.*

Hardware, performance and efficiency

- 1RU switches with up to 48 line-rate 1/2.5GbE RJ-45 ports and four integrated 25GbE SFP28 ports.
- Up to 48 ports of 30W PoE including 24 ports which can scale up to 60W PoE.
- Up to 624 1/2.5/25GbE ports in a 12-unit stack for high-density, high-availability in IDFs, MDFs and wiring closets.
- Non-stop forwarding and fast failover in stack configurations.
- Dell Fresh Air compliance for operation in environments up to 113°F (45°C) helps reduce cooling costs in temperature constrained deployments.

*Select Networking products carry a Lifetime Limited Warranty with Basic Hardware Service (repair or replacement) for life. Repair or replacement does not include troubleshooting, configuration, or other advanced service provided by Dell EMC ProSupport. Details at <https://www.dell.com/en-us/work/shop/networkingwarranty/cp/networkingwarranty>

Deploying, configuring and managing

- USB auto-configuration rapidly deploys the switch without complex TFTP configurations or sending technical staff to remote offices.
- Management via an intuitive and familiar CLI, embedded web server (GUI), SNMP-based management console application (including Dell OpenManage Network Manager), Telnet or serial connection.
- Private VLAN extensions and Private VLAN Edge support.
- AAA authorization, TACACS+ accounting and RADIUS support for comprehensive secure access support.
- Authentication tiering allows network administrators to tier port authentication methods such as 802.1x, MAC authentication.
- Bypass and Captive Portal in priority order so that a single port can provide flexible access and security.
- Achieve high availability and full bandwidth utilization with MLAG and support firmware upgrades without taking the network offline.
- Layer 3 Standard IPv4 and IPv6 functionality including static routing, RIP, and OSPF support.
- VXLAN-Lite support in hardware only (can be used if enabled by Open Networking (ON) partner network operating system).

Product	Description
N2200-ON Series	<p>OS6 Options (with pre-installed OS6 NOS)</p> <ul style="list-style-type: none"> • N2224X-ON IO/PS airflow with OS6: 24x RJ45 10M/100M/1G/2.5G auto-sensing ports, 4x SFP28 ports, 2x 40G QSFP+ ports, 1x 550W PSU included • N2224X-ON PS/IO airflow with OS6: 24x RJ45 10M/100M/1G/2.5G auto-sensing ports, 4x SFP28 ports, 2x 40G QSFP+ ports, 1x 550W PSU included • N2224PX-ON IO/PS airflow with OS6: 12x RJ45 10M/100M/1G/2.5G 802.3at (up to 30W) PoE auto-sensing ports, 12x RJ45 10M/100M/1G/2.5G 802.3bt Type-3 (up to 60W) PoE auto-sensing ports, 4x SFP28 ports, 2x 40G QSFP+ ports, 1x 1050W PSU included • N2248X-ON IO/PS airflow with OS6: 48x RJ45 10M/100M/1G/2.5G auto-sensing ports, 4x SFP28 ports, 2x 40G QSFP+ ports, 1x 550W PSU included • N2248X-ON PS/IO airflow with OS6: 48x RJ45 10M/100M/1G/2.5G auto-sensing ports, 4x SFP28 ports, 2x 40G QSFP+ ports, 1x 550W PSU included • N2248PX-ON IO/PS airflow with OS6: 24x RJ45 10M/100M/1G/2.5G 802.3at (up to 30W) PoE auto-sensing ports, 24x RJ45 110M/100M/1G/2.5G 802.3bt Type-3 (up to 60W) PoE auto-sensing ports, 4x SFP28 ports, 2x 40G QSFP+ ports, 1x 1600W PSU included
Power cords	C13 to NEMA 5-15, 3M C13 to C14, 2M
Power shelves (optional)	C13 to NEMA 5-15, 3M C13 to C14, 2M
Power supplies (optional)	<p>550W AC hot swappable with IO/PS airflow, adds redundancy to N2224X-ON, N2248X-ON 550W AC hot swappable with PS/IO airflow, adds redundancy to N2224X-ON, N2248X-ON 1050W AC hot swappable with IO/PS airflow, adds redundancy and/or extends PoE budget for N2224X-ON. Also used with MPS-1S shelf, MPS-3S Shelf 1600W AC hot swappable with IO/PS airflow, adds redundancy and/or extends PoE budget for N2248PX-ON. Also used with MPS-1S shelf, MPS-3S Shelf 2000W-AC hot swappable with IO/PS airflow, extends PoE budget, used with MPS1S Shelf, MPS-3S Shelf **</p> <p>550W DC hot swappable with IO/PS airflow, adds redundancy to N2224X-ON, N2248X-ON ** 1300W DC hot swappable with IO/PS airflow, adds redundancy and/or extends PoE budget for N2224PX-ON, N2248PX-ON **</p>
Optics	<p>Transceiver, SFP, 1000BASE-T *** Transceiver, SFP, 1000BASE-SX *** Transceiver, SFP, 1000BASE-LX *** Transceiver, SFP, 1000BASE-ZX *** Transceiver, SFP+ 10GbE, USR (MMF upto 100m) **** Transceiver, SFP+ 10GbE, SR (MMF upto 400m) **** Transceiver, SFP+ 10GbE, LR (SMF 10 km) **** Transceiver, SFP+ 10GbE, ER SMF 40 km) **** Transceiver, SFP+ 10GbE, ZR (SMF 80 km) **** Transceiver, SFP+ 10GbE, BASE-T GEN2 **** Transceiver, SFP28 25GbE, LR Transceiver, SFP28 25GbE, SR-NOF Transceiver, SFP28 25GbE, ESR Transceiver, QSFP+ 40GbE, QSFP-40G-SR4 Transceiver, QSFP+ 40GbE, QSFP-40G-LR4</p>

** Planned in Roadmap

*** Auto-negotiation not supported, using 1G optics require manual configuration and all 4x10G SFP+ or 4x25G SFP28 ports to be set to same speed. 100M speed not supported.

**** Auto-negotiation not supported, using 10G cables or optics require manual configuration and all 4x25G SFP28 ports to be set to same speed. 100M/1G speed not supported.

Product	Description
Cables	10GbE, SFP+ to SFP+, Passive DAC (0.5M, 1M, 2M, 3M, 5M, 7M) 10GbE, SFP+ to SFP+, Active optical (2M, 3M, 5M, 7M, 10M,15M, 20M) 25GbE, SFP28 to SFP28, Passive DAC (1M, 2M, 3M, 5M) 25GbE, SFP28 to SFP28, Active optical (7M, 10M,15M, 20M) 40GbE, QSFP+ to QSFP+, Passive DAC (0.5M, 1M, 2M, 3M, 5M, 7M) 40GbE, QSFP+ to QSFP+, Active optical (3M, 10M)
Fans (spare)	Fan module, IO to PSU Airflow Fan module, PSU to IO Airflow (for N2224X-ON, N2248X-ON only)

Technical specifications

Hardware specifications

Physical

2 integrated rear 40GbE QSFP+ stacking ports
Out-of-band management port (10/100/1000BASE-T)
USB (Type A) port for configuration via USB flash drive
MicroUSB (Type B) console port (MicroUSB to USB connector cable included)
RJ45 console port with RS232 signaling (RJ-45 to female DB-9 connector cable included)
Auto-negotiation for speed and flow control
Auto MDI/MDIX, port mirroring
Flow-based port mirroring
Broadcast storm control
Redundant variable speed fans (field replaceable)
Air flow: I/O to power supply; Power supply to I/O options available with non-PoE models
Integrated power supply: 550W AC (N2224X-ON, N2248X-ON), 1050W AC (N2224PX-ON), 1600W AC (N2248PX-ON)
Dual firmware images on-board
Switching engine model: Store and forward

Chassis

Size (1RU, H x W x D): 1.71 in x 17.09 in x 15.75 in (power supply/fan tray handle adds additional 1.18 in)
Approximate weight (Switch with 1 PSU installed): 14.3lbs/6.5kg (N2224X-ON), 14.7lbs/6.7kg (N2224PX-ON), 15.1lbs/6.9kg (N2248X-ON), 15.8lbs/7.2kg (N2248PX-ON)
2-Post rack mounting kit

Environmental

Power supply efficiency: 80% or better in all operating modes
Max. thermal output (BTU/hr): 812 (N2224X-ON), 4495 (N2224PX-ON), 1112 (N2248X-ON), 8478 (N2248PX-ON)
Power consumption max (watts): 238W (N2224X-ON), 1318W (N2224PX-ON), 326W (N2248X-ON), 2486W (N2248PX-ON)
Operating temperature: 32° to 113°F (0° to 45°C)
Operating humidity: 95%
Storage temperature: -40° to 149°F (-40° to 65°C)
Storage relative humidity: 85%

Performance

CPU memory: 4GB
SSD: 8GB
Packet buffer memory: 4MB
Switch fabric capacity (full duplex): 480Gbps (N2224X-ON and N2224PX-ON); 600Gbps (N2248X-ON and N2248PX-ON)

Forwarding rate:

667Mpps (N2224X-ON and N2224PX-ON);
833Mpps (N2248X-ON and N2248PX-ON)
Line-rate Layer 2 switching: All (non-blocking)
Line-rate Layer 3 routing: All (non-blocking)

Network Operating System specifications

Software specifications listed below are applicable for OS6. For detailed specifications of the NOS, please contact your Dell Technologies representative

Scaling performance

MAC addresses: 32K
Static routes: 256 (IPv4)/128 (IPv6) Dynamic routes: 256 (IPv4)
Link aggregation: 128 LAG groups, 144 dynamic ports per stack, 8 member ports per LAG
Priority queues per port: 8
RIP routing interfaces: 256
VLAN routing interfaces: 128
VLANs supported: 4,094
Protocol-based VLANs: Supported
ARP entries: 4,096
NDP entries: 512
Access control lists (ACL): Supported
MAC and IP-based ACLs: Supported
Time-controlled ACLs: Supported
Max number of ACLs: 100
Max ACL rules system-wide: 3,914
Max rules per ACL: 1,023
Max ACL rules per interface (IPv4): 1,023 (ingress), 1023 (egress)
Max ACL rules per interface (IPv6): 1023 (ingress), 509 (egress)
Max VLAN interfaces with ACLs applied: 24

IEEE compliance

802.1AB LLDP
Dell Voice VLAN
Dell ISDP
802.1D Bridging, Spanning Tree
802.1p Ethernet Priority (User Provisioning and Mapping)
Dell Adjustable WRR and Strict Queue Scheduling
802.1Q VLAN Tagging, Double VLAN Tagging, GVRP
802.1S Multiple Spanning Tree (MSTP)
802.1v Protocol-based VLANs
802.1W Rapid Spanning Tree (RSTP)
Dell RSTP-Per VLAN
Dell Spanning tree optional features: STP root guard, BPDU guard, BPDU filtering
802.1X Network Access Control, Auto VLAN
802.2 Logical Link Control
802.3 10BASE-T
802.3ab Gigabit Ethernet (1000BASE-T)
802.3ac Frame Extensions for VLAN Tagging

802.3ad Link Aggregation with LACP
802.3ae 10 Gigabit Ethernet (10GBASE-X)
802.3at PoE+ (N2024P and N2048P)
802.3AX LAG Load Balancing
Dell Multi-Chassis LAG (MLAG)
Dell Policy Based Forwarding
802.3u Fast Ethernet (100BASE-TX) on Management Ports
802.3x Flow Control
802.3z Gigabit Ethernet (1000BASE-X)
ANSI LLDP-MED (TIA-1057)
MTU 9,216 bytes

General Internet protocols

General Internet protocols are supported. For a detailed list, please contact your Dell Technologies representative.

General IPv4 protocols

General IPv4 protocols are supported. For a detailed list, please contact your Dell Technologies representative.

General IPv6 protocols

General IPv6 protocols are supported. For a detailed list, please contact your Dell Technologies representative.

Layer 3 functionality

1058 RIPv1
1724 RIPv2 MIB Extension
2082 RIP-2 MD5 Auth
2453 RIPv2
1765 OSPF DB overflow
1850 OSPF MIB
2328 OSPFv2
2740 OSPFv3 (from OS6.6.2)
3137 OSPF Stub Router Advert
5187 OSPFv3 Graceful Routing Restart (from OS6.6.2)

Multicast

2365 Admin scoped IP Mcast
2932 IPv4 MIB
4541 IGMP v1/v2/v3 Snooping and Querier
IEEE 802.1ag draft 8.1 – Connectivity Fault Management

Quality of service

2474 DiffServ Field
2475 DiffServ Architecture
2597 Assured Fwd PHB
Dell Port Based QoS (TCP/UDP) Services Mode
Dell Flow Based QoS Services Mode (IPv4/IPv6)
2697 srTCM
4115 trTCM
Dell L4 Trusted Mode
Dell UDLD

IT Lifecycle Services for Networking

Experts, insights and ease

Our highly trained experts, with innovative tools and proven processes, help you transform your IT investments into strategic advantages.



Plan & Design

Let us analyze your multivendor environment and deliver a comprehensive report and action plan to build upon the existing network and improve performance.



Deploy & Integrate

Get new wired or wireless network technology installed and configured with ProDeploy. Reduce costs, save time, and get up and running fast.



Educate

Ensure your staff builds the right skills for long-term success. Get certified on Dell EMC Networking technology and learn how to increase performance and optimize infrastructure.



Manage & Support

Gain access to technical experts and quickly resolve multivendor networking challenges with ProSupport. Spend less time resolving network issues and more time innovating.



Optimize


Maximize performance for dynamic IT environments with Dell EMC Optimize. Benefit from in-depth predictive analysis, remote monitoring and a dedicated systems analyst for your network.



Retire

We can help you resell or retire excess hardware while meeting local regulatory guidelines and acting in an environmentally responsible way.

Learn more at DellTechnologies.com/Services



[Learn more](#) about Dell EMC Networking solutions



[Contact](#) a Dell Technologies Expert



[View more](#) resources



Join the conversation
with
[@DellNetworking](#)



Dell EMC PowerSwitch N3200-ON Series Switches

High performance Open networking 1GbE and 10GbE Multigigabit switches for modern campus networks

The N3200 switch series offers power-efficient and resilient 1GbE and 1/2.5/5/10GbE Multigigabit range of switching solution for advanced Layer 3 distribution for offices and campus networks. The series has high-performance capabilities and wire-speed performance utilizing a non-blocking architecture to easily handle unexpected traffic loads. Use dual internal hot-swappable 80PLUS Platinum certified power supplies for high availability and power efficiency. The switches offer simple management and scalability via an 400Gbps (full duplex) high-availability stacking architecture that allows management of up to 12 switches from a single IP address.

Modernize campus network architectures

Modernize campus network architectures with a power-efficient and resilient 1/2.5/5/10GbE switching solution with dense options of 802.3at (30W) or 802.3bt (60W/90W) PoE solutions to deliver clean power to wide range network devices such as wireless access points (APs), Voice-over-IP (VoIP) handsets, video conferencing systems, security cameras, LED luminaires and many more.

Achieve high availability and full bandwidth utilization with Multichassis Link Aggregation (MLAG). N3200 series switches support MLAG to create active/active loop-free redundancy without spanning tree. Server rooms can deliver reliable server and storage connectivity with features to help save time and avoid configuration errors. N3200 supports VRF-lite, allowing it to be partitioned into multiple virtual routers with isolated control and data planes on the same physical switch. For greater interoperability in multivendor networks, N3200 switches offer the latest open-standard protocols.

Leverage familiar tools and practices

All N-Series switches include Dell EMC Networking OS6, designed for easier deployment, greater interoperability and a lower learning curve for network administrators. OS6 common command line interface (CLI) and graphic user interface (GUI) are intuitive, so skilled network administrators can get productive quickly. N3200 switches also support the Open Network Install Environment (ONIE), enabling installation of alternate network operating systems.

Deploy with confidence at any scale

N3200 series switches help create performance assurance with a data rate up to 1560Gbps (full duplex) and a forwarding rate up to 2167Mpps. Scale easily with built-in rear stacking ports. Switch stacks of up to 624 1/2.5/5/10GbE/25GbE ports can be managed from a single screen using the highly available stacking architecture for high-density aggregation with seamless redundant availability. The N-series switches' lifetime warranty covers software upgrades, hardware repair or replacement, and optics and cables purchased with the switch.¹

¹ Select Networking products carry a Lifetime Limited Warranty with Basic Hardware Service (repair or replacement) for life. Repair or replacement does not include troubleshooting, configuration, or other advanced service provided by Dell EMC ProSupport. See details at <https://www.dell.com/en-us/work/shop/networkingwarranty/cp/networkingwarranty>

Hardware, performance and efficiency

- 1GbE Switches: 1RU switches with up to 48 line-rate 1GbE ports of copper or fiber, and four integrated 10GbE SFP+ ports. PoE variants with up to 48 ports of 802.3at (30W) PoE.
- Multigig Switches: 1RU switches with up to 48 line-rate 1G/2.5G/ 5G/10GbE copper ports with four integrated 25GbE SFP28 ports. PoE variants with up to 48 ports of 802.3bt (90W) PoE.
- 400Gbps stacking bandwidth using two 100GbE QSFP28 integrated rear stacking ports.
- Available with dual 80PLUS Platinum certified hot swappable internal power supplies. Optional external power supply to extend PoE budgets on specific models.
- Variable speed fan operation helps decrease cooling and power costs.
- Energy-Efficient Ethernet and lower power PHYs reduce power to inactive ports and idle links, providing energy savings from the power cord to the port.
- Dell EMC Fresh Air compliance for operation in environments up to 113°F (45°C) reduces cooling costs.

Deploying, configuring and managing

- USB auto-configuration rapidly deploys the switch without complex TFTP configurations or sending technical staff to remote offices.
- Management via an intuitive and familiar CLI, embedded web server (GUI), SNMP-based management console application (including Dell EMC OpenManage Network Manager), Telnet or serial connection.
- Private VLAN extensions and Private VLAN Edge support.
- AAA authorization, TACACS+ accounting and RADIUS support for comprehensive secure access support.
- Authentication tiering allows network administrators to tier port authentication methods such as 802.1x, MAC Authentication Bypass and Captive Portal in priority order so that a single port can provide flexible access and security.
- Achieve high availability and full bandwidth utilization with MLAG and support firmware upgrades without taking the network offline.
- Layer 3 Advanced IPv4 and IPv6 functionality including BGP, VRF, BFD, PIM-SM/DM/SSM, IGMP/MLD, RIPv1/v2, OSPFv2/v3
- VXLAN support in hardware only ²
- MACsec support in N3248PXE-ON hardware only ²

² Can be used if enabled by ON partner network operating system.

Product	Description
N3200 series	<p>OS6 Options (with pre-installed OS6 NOS)</p> <ul style="list-style-type: none"> N3208PX-ON IO/PS Airflow, with OS6: 4x RJ45 10M/100M/1G/2.5G/5G 802.3bt (up to 90W) PoE auto-sensing ports, 4x 10M/100M/1000Mb 802.3bt (up to 90W) PoE autosensing ports, 2x 10G SFP+ ports, 1x 320W AC PSU included N3224T-ON IO/PS Airflow, with OS6: 24x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included N3224T-ON PS/IO Airflow, with OS6: 24x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included N3224F-ON IO/PS Airflow, with OS6: 24x 1G SFP, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included N3224P-ON IO/PS Airflow, with OS6: 24x RJ45 10/100/1000Mb 802.3at (up to 30W) PoE auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 1050W AC PSU included N3224PX-ON IO/PS Airflow, with OS6: 24x RJ45 10M/100M/1G/2.5G/5G/10G 802.3bt (up to 90W) PoE auto-sensing ports, 4x 25G SFP28 ports, 2X 100G QSFP28 ports, 1x 1600W AC PSU included N3248TE-ON IO/PS Airflow, with OS6: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included N3248TE-ON PS/IO Airflow, with OS6: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included N3248P-ON IO/PS Airflow, with OS6: 48x RJ45 10/100/1000Mb 802.3at (up to 30W) PoE auto-sensing ports; 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 1050W AC PSU included N3248X-ON IO/PS Airflow, with OS6: 48x RJ45 10M/100M/1G/2.5G/5G/10G auto-sensing ports, 4x 25G SFP28 ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included N3248X-ON PS/IO Airflow, with OS6: 48x RJ45 10M/100M/1G/2.5G/5G/10G auto-sensing ports, 4x 25G SFP28 ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included N3248PXE-ON IO/PS Airflow, with OS6: 48x RJ45 10M/100M/1G/2.5G/5G/10G 802.3bt (up to 90W) PoE auto-sensing ports; 4x 25G SFP28 ports, 2X 100G QSFP28 ports, 1x 1600W AC PSU included <p>NO-OS Options (no pre-installed NOS, recommended for use with Enterprise SONiC Distribution by Dell Technologies)</p> <ul style="list-style-type: none"> N3248TE-ON IO/PS Airflow, NO-OS: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included ² N3248TE-ON PS/IO Airflow, NO-OS: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included ² <p>OS10 Options (with pre-installed OS10 NOS)</p> <ul style="list-style-type: none"> N3248TE-ON IO/PS Airflow, with OS10: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 1x 550W AC PSU included N3248TE-ON PS/IO Airflow, with OS10: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 1x 550W AC PSU included
Power cords	<p>C15 to NEMA 5-15, 1.8M (N3208PX-ON only) C13 to NEMA 5-15, 3M (all other N3200 platforms) C13 to C14, 2M (all other N3200 platforms)</p>
Power shelves (optional)	<ul style="list-style-type: none"> MPS-1S Shelf, External power shelf to hold 1 PSU (any of 1050W AC, 1600W AC, 2000W AC, 1300W DC), Extends PoE budget for N3224PX-ON, N3248P-ON, N3248PXE-ON ³ MPS-3S Shelf, External power shelf to hold up to 3 PSUs (any combination of 1050W AC or 1600W AC or 2000W AC PSUs, or up to three 1300W DC PSUs), Extends PoE budget for N3224PX-ON, N3248P-ON, N3248PXE-ON ³

Product	Description
Power supplies (optional)	<ul style="list-style-type: none"> • 320W AC external power adapter, adds redundancy and/or extends PoE budget for N3208PX-ON • 550W AC hot swappable with IO/PS airflow, adds redundancy to N3224T-ON, N3224F-ON, N3248TE-ON, N3248X-ON • 550W AC hot swappable with PS/IO airflow, adds redundancy to N3224T-ON, N3248TE-ON, N3248X-ON • 1050W AC hot swappable, adds redundancy and/or extends PoE budget for N3224P-ON, N3248P-ON. Also used with MPS-1S shelf, MPS-3S Shelf • 1600W AC hot swappable, adds redundancy and/or extends PoE budget for N3224PX-ON, N3248PXE-ON. Also used with MPS-1S shelf, MPS-3S Shelf • 2000W AC hot swappable, extends PoE budget, used with MPS-1S Shelf, MPS-3S Shelf ³ • 550W DC hot swappable with IO/PS airflow, adds redundancy to N3224T-ON, N3224F-ON, N3248TE-ON, N3248X-ON • 550W DC hot swappable with PS/IO airflow, adds redundancy to N3224T-ON, N3248TE-ON, N3248X-ON • 1300W DC hot swappable, adds redundancy and/or extends PoE budget for N3224P-ON, N3248P-ON, N3224PX-ON, N3248PXE-ON ³
Optics	<p>Transceiver, SFP, 1000BASE-T ⁴</p> <p>Transceiver, SFP, 1000BASE-SX ⁴</p> <p>Transceiver, SFP, 1000BASE-LX ⁴</p> <p>Transceiver, SFP, 1000BASE-ZX ⁴</p> <p>Transceiver, SFP+ 10GbE, USR (MMF upto 100m) ⁵</p> <p>Transceiver, SFP+ 10GbE, SR (MMF upto 400m) ⁵</p> <p>Transceiver, SFP+ 10GbE, LRM (MMF 220m) ⁵, for SFP+ ports only</p> <p>Transceiver, SFP+ 10GbE, LR (SMF 10 km) ⁵</p> <p>Transceiver, SFP+ 10GbE, ER SMF 40 km) ⁵</p> <p>Transceiver, SFP+ 10GbE, ZR (SMF 80 km) ⁵</p> <p>Transceiver, SFP+ 10GbE, BASE-T GEN2 ⁵</p> <p>Transceiver, SFP28 25GbE, LR</p> <p>Transceiver, SFP28 25GbE, SR-NOF</p> <p>Transceiver, SFP28 25GbE, ESR</p> <p>Transceiver, QSFP28 100GbE, Q28-100G-SR4-HG</p> <p>Transceiver, QSFP28 100GbE, Q28-100G-LR4-G3</p>
Cables	<p>10GbE, SFP+ to SFP+, Passive DAC (0.5M, 1M, 2M, 3M, 5M, 7M) ⁵</p> <p>10GbE, SFP+ to SFP+, Active optical (2M, 3M, 5M, 7M, 10M, 15M, 20M) ⁵</p> <p>25GbE, SFP28 to SFP28, Passive DAC (1M, 2M, 3M, 5M)</p> <p>25GbE, SFP28 to SFP28, Active optical (7M, 10M, 15M, 20M)</p> <p>100GbE, QSFP28 to QSFP28, Passive DAC (0.5M, 1M, 2M, 3M, 5M)</p>
Fans (spare)	<p>Fan module, IO to PSU Airflow</p> <p>Fan module, PSU to IO Airflow (for N3224T-ON, N3248TE-ON, N3248X-ON only)</p>

³Planned in Roadmap

⁴Auto-negotiation not supported, using 1G optics require manual configuration and all 4x10G SFP+ or 4x25G SFP28 ports to be set to same speed. 100M speed not supported.

⁵Auto-negotiation not supported, using 10G cables or optics require manual configuration and all 4x25G SFP28 ports to be set to same speed. 100M/1G speed not supported.

Hardware specifications

Physical

2 integrated rear 100GbE QSFP28 stacking ports (except N3208PX-ON)
 Out-of-band management port (10/100/1000BASE-T)
 USB (Type A) port for configuration via USB flash drive
 MicroUSB (Type B) console port (MicroUSB to USB connector cable included)
 RJ45 console port with RS232 signaling (RJ-45 to female DB-9 connector cable included)
 Auto-negotiation for speed and flow control
 Auto-MDI/MDIX, port mirroring
 Flow-based port mirroring Broadcast storm control
 Energy-Efficient Ethernet per port settings
 Redundant variable speed fans
 Air flow: I/O to power supply
 Power supply:
 Integrated 320W (N3208PX-ON), 550W (N3224T-ON, N3224F-ON, N3248TE-ON, N3248X-ON), 1050W (N3224P-ON, N3248P-ON), 1600W (N3224PX-ON, N3248PX-ON)
 Dual firmware images on-board
 Switching engine model: Store and forward

Chassis

Size (1RU, H x W x D):
 N3208PX-ON: 1.71 in x 11 in x 12.28 in;
 All other models: 1.71 in x 17.09 in x 15.75 in (power supply/fan tray handle adds add'l 1.18 in)
 Approximate weight (Switch with 1 PSU installed):
 8.44lbs/3.83kg (N3208PX-ON),
 13.75lbs/6.24kg (N3224T-ON),
 14.25lbs/6.46kg (N3224F-ON),
 15.6lbs/7.08kg(N3224P-ON),
 16lbs/7.26kg (N3224PX-ON),
 15.4lbs/6.99kg (N3248TE-ON),
 16.7lbs/7.57kg (N3248P-ON),
 16.1lbs/7.3kg (N3248X-ON),
 17.6lbs/7.98kg (N3248PX-ON)
 2-post rack mounting kit

Environmental

Power supply efficiency: 87% or better in all operating modes
 Max. thermal output (BTU/hr):
 2821 (N3208PX-ON), 686 (N3224T-ON), 764 (N3224F-ON), 3220 (N3224P-ON), 9344 (N3224PX-ON), 723 (N3248TE-ON), 5719 (N3248P-ON), 1637 (N3248X-ON), 18224 (N3248PX-ON)
 Power consumption max (watts):
 900 (N3208PX-ON), 201 (N3224T-ON), 224 (N3224F-ON), 944 (N3224P-ON), 2740 (N3224PX-ON), 212 (N3248TE-ON), 1677 (N3248P-ON), 480 (N3248X-ON), 5344 (N3248PX-ON)
 Operating temperature: 32° to 113°F (0° to 45°C)
 Operating relative humidity: 95%
 Storage temperature: -40° to 158°F (-40° to 70°C)
 Storage relative humidity: 95%

Performance

CPU memory: 4GB
 SSD: 8GB (32GB for N3248TE-ON)
 Packet buffer memory:
 8MB (4MB for N3208PX-ON and 32MB for N3248X-ON and N3248PX-ON)

Switch fabric capacity (full-duplex):
 88Gbps (N3208PX-ON),
 528Gbps (N3224T-ON, N3224F-ON, N3224P-ON),
 576Gbps (N3248TE-ON, N3248P-ON),
 1080Gbps (N3224PX-ON),
 1560Gbps (N3248X-ON, N3248PX-ON)
 Forwarding rate:
 122Mpps (N3208PX-ON),
 733Mpps (N3224T-ON, N3224F-ON, N3224P-ON),
 800Mpps (N3248TE-ON, N3248P-ON),
 1500Mpps (N3224PX-ON),
 2167Mpps (N3248X-ON, N3248PX-ON)
 Line-rate Layer 2 switching: All (non-blocking)
 Line-rate Layer 3 routing: All (non-blocking)

Network Operating System specifications

Software specifications listed below are applicable for OS6. For detailed specifications of NOS, please contact your Dell Technologies representative.

Scaling performance

MAC addresses: 32K
 Link aggregation:
 128 LAG groups, 144 dynamic ports per stack, 8 member ports per LAG
 Priority queues per port: 8
 Static routes: 1,024 (IPv4)/1,024 (IPv6)
 Dynamic routes: 8,158 (IPv4)/4,096 (IPv6)
 OSPF routing interfaces: 8,158
 RIP routing interfaces: 512
 ECMP next hops per route: 16
 ECMP groups: 1024
 VLAN routing interfaces: 128
 VLANs supported: 4,094
 Protocol-based VLANs: Supported
 Multicast forwarding entries:
 1,536 (IPv4), 512 (IPv6)
 ARP entries: 6,144
 NDP entries: 2,560
 Access control lists (ACL): Supported
 MAC and IP-based ACLs: Supported
 Time-controlled ACLs: Supported
 Max number of ACLs: 100
 Max ACL rules system-wide: 3,914
 Max rules per ACL: 1,023
 Max ACL rules per interface (IPv4):
 1,023 (ingress), 511 (egress)
 Max ACL rules per interface (IPv6):
 1,021 (ingress), 509 (egress)
 Max VLAN interfaces with ACLs applied: 24

IEEE compliance

802.1AB LLDP
 Dell Voice VLAN
 Dell ISDP
 802.1D Bridging, Spanning Tree
 802.1p Ethernet Priority (User Provisioning and Mapping)
 Dell Adjustable WRR and Strict Queue Scheduling
 802.1Q VLAN Tagging, Double VLAN Tagging, GVRP
 802.1S Multiple Spanning Tree (MSTP)
 802.1v Protocol-based VLANs
 802.1W Rapid Spanning Tree (RSTP)
 Dell RSTP-Per VLAN
 Dell Spanning tree optional features: STP root guard, BPDU guard, BPDU filtering
 802.1X Network Access Control, Auto VLAN
 802.2 Logical Link Control
 802.3 10BASE-T
 802.3ab Gigabit Ethernet (1000BASE-T)
 802.3ac Frame Extensions for VLANTagging
 802.3ad Link Aggregation with LACP
 802.3ae 10 Gigabit Ethernet (10GBASE-X)

802.3at PoE (N3224P-ON, N3248P-ON, N3208PX-ON, N3224PX-ON, N3248PX-ON)
 802.3bt PoE (N3208PX-ON, N3224PX-ON, N3248PX-ON)
 802.3AX LAG Load Balancing
 Dell Multi-Chassis LAG (MLAG)
 Dell Policy Based Forwarding
 802.3az Energy Efficient Ethernet (EEE)
 802.3u Fast Ethernet (100BASE-TX) on management ports
 802.3x Flow Control
 802.3z Gigabit Ethernet (1000BASE-X)
 802.3bz 1G/2.5G/5G/10G
 ANSI LLDP-MED (TIA-1057)
 Dell EqualLogic iSCSI Auto-configuration
 MTU 9,216 bytes

General Internet protocols

General Internet protocols are supported. For a detailed list, please contact your Dell Technologies representative.

General IPv4 protocols

General IPv4 protocols are supported. For a detailed list, please contact your Dell Technologies representative.

General IPv6 protocols

General IPv6 protocols are supported. For a detailed list, please contact your Dell Technologies representative.

Layer 3 functionality

1058 RIPv1
 1724 RIPv2 MIB Extension
 1765 OSPF DB overflow
 1850 OSPF MIB
 2082 RIP-2 MD5 Auth
 2328 OSPFv2
 2338 VRRP
 2370 Opaque
 Dell Policy Based Routing
 2453 RIPv2
 2740 OSPFv3
 2787 VRRP MIB
 3101 NSSA
 3137 OSPF Stub Router Advert
 3623 Graceful Restart
 3768 VRRP
 4271 BGP
 5187 OSPFv3 Graceful Routing Restart

Multicast

1112 IGMPv1
 2236 IGMPv2
 2365 Admin scoped IP
 2710 MLDv1
 2932 IPv4 MIB
 2933 IGMP MIB
 3810 MLDv2
 3973 PIM-DM
 4541 IGMP v1/v2/v3 Snooping and Querier
 5060 PIM MIB
 5061 PIM MIB
 3376 IGMPv3
 Dell Static IP Multicast
 Draft-ietf-pim-sm-bsr-05
 Draft-ietf-idmr-dvmrp-v3-10 DVMRP
 Draft-ietf-magma-igmp-proxy-06.txt
 IGMP/MLD Proxying
 Draft-ietf-magma-igmpv3-and-routing-05.txt
 draft-ietf-idmr-dvmrp-mib-11
 draft-ietf-magma-mgmd-mib-05
 draft-ietf-pim-bsr-mib-06
 IEEE 802.1ag draft 8.1 – Connectivity Fault Management (CFM)
 IEEE 802.1p GMRP Dynamic L2 Multicast Registration

Technical specifications

Quality of service

2474	DiffServ Field	2295	Transport Content Negotiation	5246	TLS v1.2
2475	DiffServ Architecture	2296	Remote Variant Selection	6101	SSL
2597	Assured Fwd PHB	2576	Coexistence between SNMPv1/v2/v3	6398	IP Router Alert
Dell	Port Based QoS Services (TCP/UDP) Mode	2578	SMLv2	Dell	Enterprise MIB supporting routing features
Dell	Red/WRED	2579	Textual Conventions for SMLv2		draft-ietfhubmib- etherifmib- v3-00.txt (Obsoletes RFC 2665)
Dell	Flow Based QoS Services	2580	Conformance Statements for SMLv2		
Dell	Audio Video Bridging Mode (IPv4/IPv6)	2613	RMON MIB		
Dell	UDLD	2618	RADIUS Authentication MIB		
2697	srTCM	2620	RADIUS Accounting MIB		
4115	trTCM	2665	Ethernet-like Interfaces MIB		
		2666	Identification of Ethernet chipsets		
		2674	Extended Bridge MIB		
		2737	ENTITY MIB		
		2818	HTTP over TLS		
		2819	RMON MIB (groups 1, 2, 3, 9)		
		2856	Text Conv. For High Capacity Data Types		

Network Management and Security

Dell	L4 Trusted Mode		Interfaces MIB		
1155	SMLv1		RADIUS		
1157	SNMPv1	2863	RADIUS Accounting		
1212	Concise MIB Definitions	2865	RADIUS Attributes for Tunnel Prot.		
1213	MIB-II	2866	RADIUS Extensions		
1215	SNMP Traps	2868	Internet Standard Mgmt. Framework		
1286	Bridge MIB	2869	SNMP Management Framework		
1442	SMLv2	3410	Message Processing and Dispatching		
1451	Manager-to-Manager MIB	3411	SNMP Applications		
1492	TACACS+	3412	User-based security model		
1493	Managed objects for Bridges MIB	3413	View-based control model		
1573	Evolution of Interfaces	3414	SNMPv2		
1612	DNS Resolver MIB Extensions	3415	Transport Mappings		
1643	Ethernet-like MIB	3416	SNMP MIB		
1757	RMON MIB	3417	RMON MIB		
1867	HTML/2.0 Forms with file upload extensions	3418	802.1X with RADIUS		
1901	Community-based SNMPv2	3577	Registry of RMON MIB		
1907	SNMPv2 MIB	3580	Randomness Requirements		
1908	Coexistence between SNMPv1/v2	3737	UDP MIB		
2011	IP MIB	4086	SSHv2 Protocol		
2012	TCP MIB	4113	SSHv2 Authentication		
2013	UDP MIB	4251	SSHv2 Transport		
2068	HTTP/1.1	4252	SSHv2 Connection Protocol		
2096	IP Forwarding Table MIB	4253	SSHv2 Transport Layer Protocol		
2233	Interfaces Group using SMLv2	4254	LDAP Extensions		
2246	TLS v1	4419	SECSH Public Key File Format		
2271	SNMP Framework MIB	4521			
		4716			

Other certifications

N-Series products have the necessary features to support a PCI compliant network topology.

Regulatory, environment and other compliance

Safety and emissions

Australia/New Zealand: ACMA RCA Class A
 Canada: ICES Class A; cUL
 China: CCC Class A; NAL
 Europe: CE Class A
 Japan: VCCI Class A
 USA: FCC Class A; NRTL UL; FDA 21 CFR 1040.10 and 1040.11
 Eurasia Customs Union: EAC Germany: GS mark
 Product meets EMC and safety standards in many countries inclusive of USA, Canada, EU, Japan, China. For more country-specific regulatory information, and approvals, please see your Dell Technologies representative.

RoHS

Product meets RoHS compliance standards in many countries inclusive of USA, EU, China, and India. For more country-specific RoHS compliance information, please see your Dell Technologies representative.
 EU WEEE
 EU Battery Directive
 REACH

Energy

Japan: JEL

IT Lifecycle Services for Networking

Experts, insights and ease

Our highly trained experts, with innovative tools and proven processes, help you transform your IT investments into strategic advantages.



Plan & Design

Let us analyze your multivendor environment and deliver a comprehensive report and action plan to build upon the existing network and improve performance.



Deploy & Integrate

Get new wired or wireless network technology installed and configured with ProDeploy. Reduce costs, save time, and get up and running fast.



Educate

Ensure your staff builds the right skills for long-term success. Get certified on Dell EMC Networking technology and learn how to increase performance and optimize infrastructure.



Manage & Support

Gain access to technical experts and quickly resolve multivendor networking challenges with ProSupport. Spend less time resolving network issues and more time innovating.



Optimize


Maximize performance for dynamic IT environments with Dell EMC Optimize. Benefit from in-depth predictive analysis, remote monitoring and a dedicated systems analyst for your network.



Retire

We can help you resell or retire excess hardware while meeting local regulatory guidelines and acting in an environmentally responsible way.

Learn more at DellTechnologies.com/Services



[Learn more](#) about Dell EMC Networking solutions



[Contact](#) a Dell Technologies Expert



[View more](#) resources



Join the conversation with [@DellNetworking](#)